

Carpet Sign

Tweet

Technical information

production method:	tufted
pile material:	38,5% wool/19,5% linen/14% silk 14% viscose en 14% cotton
pile height:	10
pile weight gr/m2:	2500
number of standard colours:	20
Customer own colour:	yes
maximum size without seams:	430 x 470 cm
Special shapes & design:	available on request
cleaning :	www.james.eu
design :	Carpet Sign studio

Durability

- This rug can be used with under-floor heating, unless it is a wall to wall carpet.
- Connect has officially been tested and is suitable for residential and contract use.

Maintenance

- It is important to vacuum your rug at least once a week to prolong its durability.
- a new rug will produce fluff, but this is temporary. This fluff does not affect the quality of your rug.
- The ideal air humidity for wool is around 50%. Please note that if the air humidity is below 50%, the material becomes dry and its natural elasticity will decrease.
- In order to prevent wool from drying out, we recommend misting your woollen rug with water regularly.
- In order to prevent heavy use on one particular location, we recommend turning your rug around once in a while.
- Due to our use of natural materials, slight colour differences may occur.
- We offer personal maintenance advice via www.james.eu

Underlay

- For rugs to be placed on wooden floors or natural stone floors (e.g. marble), the use of an underlay is strongly recommended.

Warranty

- Carpet Sign offers 5 years warranty (excluding shading)

Cut/Loop pile:



Loop pile:



Carpet Sign bv
Bonksel 1
5721 TP Asten
The Netherlands

T. +31 (0)493 696 723
F. +31 (0)493 69 09 69
info@carpetsign.nl
www.carpetsign.nl