

# Carpet Sign

## Surfaces

### Technical information

production method:	tufted - loop pile
pile material:	65% wool - 35% viscose
pile height:	8-20 mm
pile weight gr/m2:	2350-3600
number of standard colours:	13 colours
maximum size without seams:	430 x 470 cm
Special shapes & design:	available on request
cleaning :	www.james.eu
design :	Carpet Sign studio

### Durability

- Wool has a natural elasticity and is also naturally resistant to dirt.
- This rug can be used with under-floor heating, unless it is a wall to wall carpet.
- Surfaces is suitable for residential and (light)contract use e.g. lobby etc. Not suitable for (office)castor chairs.

### Fire safety

Surfaces is made of 65% pure wool, which is naturally flame retardant.

### Maintenance

- It is important to vacuum your rug at least once a week to prolong its durability.
- The ideal air humidity for wool is around 50%. Please note that if the air humidity is below 50%, the material becomes dry and its natural elasticity will decrease.
- In order to prevent heavy use on one particular location, we recommend turning your rug around once in a while.
- Due to our use of natural materials, slight colour differences may occur.
- We offer personal maintenance advice via [www.james.eu](http://www.james.eu)

### Underlay

- For rugs to be placed on wooden floors or natural stone floors (e.g. marble), the use of an underlay is strongly recommended. Floor damage that occurs as a result of not using underlay are rejected at once.

### Warranty

- Carpet Sign offers 5 years warranty (excluding shading)

