

# Carpet Sign

## Filasse

### Technical information

production method:	tufted
pile material:	75% wool en 25% linen
pile height:	45
pile weight gr/m2:	3300
number of standard colours:	10x
Customer own colour:	available on request
maximum size without seams:	430 x 470 cm
Special shapes & design:	available on request
cleaning :	www.james.eu
design :	Carpet Sign studio

### Durability

- This rug can be used with under-floor heating, unless it is a wall to wall carpet.
- Filasse has officially been tested and is suitable for residential and (light)contract use. Not suitable for (office)castor chairs.
- Linen has no resilience. This may lead to 'retraction' of the linen yarns.

### Fire safety

Filasse is made of 75% pure wool, which is naturally flame retardant.

### Maintenance

- It is important to vacuum your rug at least once a week to prolong its durability.
- a new rug will produce fluff, but this is temporary. This fluff does not affect the quality of your rug.
- The ideal air humidity for wool is around 50%. Please note that if the air humidity is below 50%, the material becomes dry and its natural elasticity will decrease.
- In order to prevent wool from drying out, we recommend misting your woollen rug with water regularly.
- In order to prevent heavy use on one particular location, we recommend turning your rug around once in a while.
- Due to our use of natural materials, slight colour differences may occur.
- We offer personal maintenance advice via [www.james.eu](http://www.james.eu)

### Underlay

- For rugs to be placed on wooden floors or natural stone floors (e.g. marble), the use of an underlay is strongly recommended.

### Warranty

- Carpet Sign offers 5 years warranty (excluding shading)

